DoP PETTG101 page 1/3

PETTG101



Issued in accordance with the Construction Products Regulation (CPD) 305/2011/EU. pgb-Europe nv hereby declares that the products mentioned below comply with the requirements of:

EN 14592 2008+A1 2012 - Timber structures - Dowel-type fasteners

1. Unique identification code of the product-type:

PETTG A2

2. Type or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

see annex 1 to this document

3. Intended uses of the construction product, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer:

Generic type:	Wood construction screw with cutting point, partial thread with flutes		
	and milling segment on the shank, flange head, T-drive recess		
Material:	Stainless steel A2 grade 50 according to EN ISO 3506-1		
Service class:	Service class 1, 2 and 3 according to EN 1995-1-1		
Fire resistance:	NPD		
Reaction to fire:	Classification A1 according to EN13501-1		
Intended use:	Screws for load-bearing timber structures		

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5):

pgb-Europe nv – Gontrode Heirweg 170 – 9090 Melle – Belgium

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

NOT RELEVANT

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

In case of the declaration of performance concerning a construction product covered by a harmonized

standard: EN 14592:2008 +A1-2012 performed by: HFB Engineering GMBH

Zschortauer Straße 42

04129 Leipzig

under system: 3

and issued: Initial Type Test report n° 311002167/1/2013

pgb

DoP PETTG101 page 2 / 3

8. In case of the declaration of performance concerning a construction product for which European Technical Assessment has been issued:

NOT RELEVANT

9. Declared performance:

		Performance
Essential characteristics		
		Ø 8
Characteristic yield moment M _{y,k}	[Nmm]	20040
Characteristic withdrawal parameter f _{ax,k}	[N/mm²]	22,3 1
Wood density	[, 4,]	17,8 ²
Wood density	ρk [kg/m³]	450
Characteristic head pull-through parameter fhead,k	[N/mm ²]	14,3
Wood density	ρk [kg/m³]	450
Characteristic tensile capacity f _{tens,k}	[kN]	13,80
Characteristic torsional strength f _{tor,k}	[Nm]	19,64
		4,22 ³
Characteristic torsional resistance R _{tor,k}	[Nm]	
•		7,39 ⁴
Characteristic torsional ratio (pk 450 kg/m³)	[-]	4,6 / 2,7

Tested according to Harmonized Technical Specification EN 14592 2008+A1:2012.

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Place and date of issue	Signature		
Melle, 10/10/2013	nv pgb-Europe sa Gontrode Heirweg 170 9090 MELLE BE 0425 888 396	Johannes Heye, product manager	



Annex 1: Product overview





